

ZKBio910P Series All-in-One Biometric Smart POS Terminal



Features

- Power-efficient Intel® Celeron® J1900 2.0 GHz Quad-Core processor
- 15" Bezel-Free True-Flat PCAP touch screen
- Optional Intel® Core™ i3 or i5 processor
- Fingerprint verification (optional)
- Standard with 80mm thermal printer
- Modular design with aluminium alloy material
- VFD and second display can be adjusted in angle
- Easy to hide cables and fanless design

Optional



Magnetic Stripe
Card Reader



Barcode Scanner



Fanless Design



Thermal Printer



VFD Customer Display



Fingerprint Module

Specifications

Model Name	ZKBio910P	ZKBio930P	ZKBio950P
System			
Processor	Intel® Celeron J1900 Quad-Core Processor (2.0 GHz)	Intel® Core™ i3 Processor(1.7GHz)	Intel® Core™ i5 Processor (1.6 GHz up to 2.6 GHz)
System Memory	4GB Standard, DDR3L 1666MHz		
Storage Device	64GB SSD Standard, 1*2.5" HDD & 2.5" SSD		
OS Supported	Windows 7, Windows 8, Windows 10 IoT Enterprise, POS Ready 7, Linux		
Audio	Realtek ALC662		
Display and Touch			
Type	15" TFTLCD, LED Backlight		
Resolution	1024*768		
Touch Screen	Projected capacitive touch screen		
Customer Display	LED (8C digital tube)		
External I/O Ports			
VGA	1*DB-15		
USB	4*USB 2.0 & 1*USB 3.0	5*USB 2.0 & 1*USB3.0	5*USB 2.0 & 1*USB 3.0
COM	3	0	0
HDMI	0	1	1
LAN	1		
Audio	1*line-out	1*line-out, 1*mic In	1*line-out, 1*mic In
Cash Drawer	1	0	0
Physical Environment			
Operating Temperature	0°C to 35°C at 20% to 80% RH		
Storage Temperature	-20°C to 55°C at 20% to 80% RH		
Power Supply	Adaptor 12V DC 5A		
Certification	CE, FCC		
Packing Dimensions	41.7*28*57(L*W*H)		
Net Weight	12.8kg		
Packing Weight	14.2kg		
Material	Aluminum alloys, ABS		
Color	Black		
Options & Peripherals			
2nd Display	8"/10" TFT LCD		
Customer Display	20 columns * 2 lines		
MSR	3 tracks		
Barcode Scanner	2D barcode scanner		
Fingerprint	USB fingerprint module		

