

NX-2KV

8MP Video Balun With 2KV Surge Protection



Key Feature

- ✓ Push interface with cable
- ✓ Mini size for easy installation
- ✓ No power required, and simplified project wiring
- ✓ Plug and play, real-time transmit CCTV HD video signal, and high quality and stable video
- ✓ Compatible with HDTVl/HDCVl/AHD/CVBS
- ✓ Transmission distance: non-POC Camera: Max. 200m, Coaxial : 300m (95% Copper)



Feature		Specification
Properties	Transmission Signal	1 channel
	Transmission Distance	Non-POC Camera: Max 200m, Coaxial: 300m (95 % Cooper)
	Category Type	UTP CAT 5E/ 6 (R<100Ω/100M)
Video Transmission Properties and Port	Coaxial Video Connector	BNC-M
	Twisted-pair Video Connector	Push
	Compatible Format	HDTVl/HDCVl/AHD/CVBS
	Resolution	720P/1080P/3MP/4MP/5MP/8MP
	Ant-interference	>60db
Protection	Coaxial Cable Connector	2KV(common-code) Per:IEC61000-4-5
	UTP Cable Connector	2KV(different-code), 2KV(common-code) Per:IEC61000-4-5
Impedance	BNC Male	75 ohms
	UTP Cable	100 ohms
Physical Properties	Shell	ABS
	Dimensions (L x W x H)	147mm x 14.5mmx 17mm , 45mm x 14.5mmx 17mm
	Weight	31.2 g
Stability	MTBF	>10000 h
Environmental	Operating Temperature	-10-55°C
	Storage Temperature	-20-70°C

Typical Application



HD CAMERA



NX-2KV



HD DVR